

**L.B. WHITE****TRADESMAN® FORCED AIR KEROSENE HEATERS**Tradesman  
K75Tradesman  
K125Tradesman  
K175Tradesman  
K210Tradesman  
K400Tradesman  
K650

|   | Tradesman<br>K75 | Tradesman<br>K125 | Tradesman<br>K175 | Tradesman<br>K210 | Tradesman<br>K400 | Tradesman<br>K650 |
|---|------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Btu/h Rating  | 75,000           | 125,000           | 175,000           | 210,000           | 400,000           | 650,000           |
| Heated Air Output (CFM)   | 265              | 520               | 600               | 650               | 1400              | 3600              |
| Pump Pressure (PSI)   | 3.8              | 5.5               | 6.5               | 8.5               | 125               | 110               |
| Fuel Consumption (max.)<br>Kerosene, #1 diesel or<br>#1 fuel oil (gal./hr.) | 0.57             | 0.95              | 1.3               | 1.6               | 3.0               | 4.9               |
| Tank Capacity (gal.)  | 5                | 10                | 13                | 13                | 29                | 50                |
| Operating Time/Tankful (hrs.)   | 8.8              | 10.5              | 10.0              | 8.0               | 9.5               | 10.0              |
| Ignition Type   | Direct Spark     | Direct Spark      | Direct Spark      | Direct Spark      | Direct Spark      | Direct Spark      |
| Electrical Supply (Volts/Hz/Phase)  | 120 / 60 / 1     | 120 / 60 / 1      | 120 / 60 / 1      | 120 / 60 / 1      | 120 / 60 / 1      | 120 / 60 / 1      |
| Amps (Cont. Oper.)  | 1.6              | 2.5               | 3.2               | 3.7               | 4.4               | 7.1               |
| Motor Horsepower  | 1/8              | 1/5               | 1/4               | 1/3               | 1/2               | 3/4               |
| Case Material<br>Enamel   | Baked<br>Enamel  | Baked<br>Enamel   | Baked<br>Enamel   | Baked<br>Enamel   | Baked<br>Enamel   | Baked             |
| Dimensions (in.) *  |                  |                   |                   |                   |                   |                   |
| Length  | 32.0             | 37.5              | 43.5              | 43.5              | 52.5              | 69.2              |
| Width   | 11.8             | 22.4              | 23.9              | 23.9              | 32.0              | 30.7              |
| Height  | 16.8             | 24.9              | 26.6              | 26.6              | 34.0              | 48.7              |
| Net Weight (lbs. – w/o fuel)  | 27.0             | 49.0              | 53.0              | 57.0              | 141.0             | 276.0             |
| Shipping Weight (lbs.)  | 30.0             | 55.0              | 60.0              | 65.0              | 155.0             | 298.0             |
| Thermostat  | S                | S                 | S                 | S                 | S                 | S                 |
| Handle(s)   | S                | S                 | S                 | S                 | S                 | S                 |
| Wheels  | –                | Pneumatic         | Pneumatic         | Pneumatic         | Pneumatic         | Semi-Pneumatic    |
| Fuel & Pump Pressure Gauges   | S / S            | S / S             | S / S             | S / S             | S / -             | S / -             |
| On/Off Switch   | S                | S                 | S                 | S                 | S                 | S                 |
| Cord Caddy  | S                | S                 | S                 | S                 | S                 | –                 |
| CSA US & Canada Certification   | Yes              | Yes               | Yes               | Yes               | Yes               | Yes               |

S = Standard



World Provider of Innovative Heating Solutions

411 Mason Street, Onalaska, WI 54650  
 (800) 345 7200  
 (608) 783 5691  
 (608) 783 6115, fax  
 www.lbwhite.com

© 2015 L.B. White Co.  
 All rights reserved.  
 All specifications are subject  
 to change without notice.